



GENERAL

KEY FEATURES

Lunawood is the original thermal treatment wood manufacturer in the world and has been pioneering thermal modification technology for over 20 years. Lunawood's thermally-modified Spruce & Pine is highly suitable for exterior cladding due to its dimensional stability, weather resistance, durability, & beautiful appearance - all achieved without chemicals through natural modification. It's renewable and PEFC certified, making it a truly sustainable choice throughout its life cycle.

REGION

Finland

WARRANTY

N/A

CERTIFICATIONS

PEFC

APPLICATIONS/USES

Exterior cladding, Interior paneling, ceilings & soffits, decking

PRODUCT SPECIFICATIONS

DURABILITY

LunaThermo-D (Class 2)
30-year expected service life

GRADE

Knotty A-grade

JANKA HARDNESS

~382 lbf

FLAME SPREAD

Class B

MOISTURE CONTENT

6-8%

FINISHES

Unfinished

NOMINAL SIZES

Luna SHP (Decking): 5/4" x 6" (32x150mm)

PRE-MILLED SIZES

Luna Triple: 5/4" x 5-1/4" (32x140mm)
Luna Duo: 5/4" x 5-1/4" (32x140mm)
Luna Trio: 4/4" x 3-1/4" (26x92mm)
Luna Femma: 4/4" x 5-1/4" (26x142mm)

BLANK NET SIZES

Luna SHP (Decking): 1" x 5-1/2" (26x140mm)

LENGTHS

9.5'-16.5' random

**Not available in Tex Gap profiles.*

www.lunawood.com/us/