



## GENERAL

### KEY FEATURES

Lunawood modifies ThermoWood® products which are grown and strengthened for nearly 80 years in Scandinavia. The renewable forest provides raw material that will last for decades. ThermoWood® products are thermally modified using only natural methods, heat and steam. ThermoWood® Spruce is most known for its dimensional stability, durability and sustainable nature. It doesn't require surface treatments, which makes it an ecological choice throughout its life cycle.

### REGION

Finland

### WARRANTY

N/A

### CERTIFICATIONS

PEFC

### APPLICATIONS/USES

Exterior cladding, Interior paneling, ceilings & soffits, decking

## PRODUCT SPECIFICATIONS

### DURABILITY

LunaThermo-D (Class 2)  
30-year expected service life

### GRADE

Knotty A-grade

### JANKA HARDNESS

~382 lbf

### FLAME SPREAD

Class B

### MOISTURE CONTENT

6-8%

### FINISHES

Unfinished, Prefinished, Nylon Brushed, Rough Sawn

### FIRE RATING

SFM 12-7A-1 (WUI Compliant)

### NOMINAL SIZES

4/4 x 4/6/8"  
8/4 x 4/6/8"

### ROUGH NET SIZES

4/4 x 6": 0.92" x 5.65" (23x143mm)

### LENGTHS

8.5'-17.5' random

### WEIGHT

1.4 lb/sf

\*Not available in Tex Gap profiles.

[www.lunawood.com/thermowood/](http://www.lunawood.com/thermowood/)